

ARX LINE 1-2



ARX 10.1

EU Stage V / U.S. EPA Phase III

OPERATING WEIGHT	1 300 kg (2,866 lb)
MAX. OPERATING WEIGHT	1 398 kg (3,082 lb)
WORKING WIDTH	900 mm (35,4 in)
ENGINE	Honda GX630

ARX 12-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	1 460 kg (3,219 lb)
MAX. OPERATING WEIGHT	1 610 kg (3,549 lb)
WORKING WIDTH	820 mm (32,3 in)
ENGINE	Kubota D1105

ARX 16-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	1 510 kg (3,329 lb)
MAX. OPERATING WEIGHT	1 655 kg (3,649 lb)
WORKING WIDTH	900 mm (35,4 in)
ENGINE	Kubota D1105

ARX 16-2 C

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	1 450 kg (3,197 lb)
MAX. OPERATING WEIGHT	1 600 kg (3,527 lb)
WORKING WIDTH	900 mm (35,4 in)
ENGINE	Kubota D1105



ARX 20-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	1 570 kg (3,461 lb)
MAX. OPERATING WEIGHT	1 715 kg (3,781 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1105

ARX LINE 2-2



ARX 23.1-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 260 kg (4,982 lb)
MAX. OPERATING WEIGHT	2 495 kg (5,501 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1105 Yanmar 3TNV80F

ARX 23.1-2 C

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 110 kg (4,652 lb)
MAX. OPERATING WEIGHT	2 310 kg (5,093 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1105 Yanmar 3TNV80F

ARX 23-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 230 kg (4,916 lb)
MAX. OPERATING WEIGHT	2 425 kg (5,346 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1803-CR

ARX 23-2 C

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 085 kg (4,597 lb)
MAX. OPERATING WEIGHT	2 285 kg (5,038 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1803-CR



ARX 23-2

EU Stage IIIA / U.S. EPA Tier 4i

OPERATING WEIGHT	2 260 kg (4,982 lb)
MAX. OPERATING WEIGHT	2 495 kg (5,501 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1803-M-DI

ARX 23-2 C

EU Stage IIIA / U.S. EPA Tier 4i

OPERATING WEIGHT	2 110 kg (4,652 lb)
MAX. OPERATING WEIGHT	2 310 kg (5,093 lb)
WORKING WIDTH	1000 mm (39,4 in)
ENGINE	Kubota D1803-M-DI



ARX 26.1-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 460 kg (5,423 lb)
MAX. OPERATING WEIGHT	2 655 kg (5,853 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1703-M-DI Yanmar 3TNV80F

ARX 26.1-2 C

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 110 kg (4,652 lb)
MAX. OPERATING WEIGHT	2 310 kg (5,093 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1703-M-DI Yanmar 3TNV80F

ARX 26-2

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 515 kg (5,545 lb)
MAX. OPERATING WEIGHT	2 710 kg (5,975 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1803-CR

ARX 26-2 C

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	2 350 kg (5,181 lb)
MAX. OPERATING WEIGHT	2 550 kg (5,622 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1803-CR



ARX 26-2

EU Stage IIIA / U.S. EPA Tier 4i

OPERATING WEIGHT	2 460 kg (5,423 lb)
MAX. OPERATING WEIGHT	2 655 kg (5,853 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1803-M-DI

ARX 26-2 C

EU Stage IIIA / U.S. EPA Tier 4i

OPERATING WEIGHT	2 300 kg (5,071 lb)
MAX. OPERATING WEIGHT	2 500 kg (5,512 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota D1803-M-DI

eARX 26-2



eDrive

OPERATING WEIGHT	2640 kg (5820 lb)
MAX. OPERATING WEIGHT	2770 kg (6110 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	eDrive (battery)

ARX LINE 4-2

PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE
FOR PRODUCT AVAILABILITY IN YOUR MARKET.



ARX 36-2

EU Stage V | U.S. EPA Tier 4F

ARX 36-2

EU Stage IIIA / U.S. EPA Tier 4I

OPERATING WEIGHT	3 785 kg (8,344 lb)	3785 kg (8344 lb)
MAX. OPERATING WEIGHT	4 075 kg (8,984 lb)	4075 kg (8984 lb)
WORKING WIDTH	1300 mm (51,2 in)	1300 mm (51,2 in)
ENGINE	Kubota D1803-CR-T	Kubota V2403-M



ARX 40-2

EU Stage V | U.S. EPA Tier 4F

ARX 40-2 C

EU Stage V | U.S. EPA Tier 4F

ARX 40-2

EU Stage IIIA / U.S. EPA Tier 4I

ARX 40-2 C

EU Stage IIIA / U.S. EPA Tier 4I

OPERATING WEIGHT	4 200 kg (9,259 lb)	4055 kg (8940 lb)	4 175 kg (9,904 lb)	4055 kg (8940 lb)
MAX. OPERATING WEIGHT	4 490 kg (9,899 lb)	4355 kg (9600 lb)	4 465 kg (9,844 lb)	4355 kg (9600 lb)
WORKING WIDTH	1300 mm (51,2 in)	1300 mm (51,2 in)	1300 mm (51,2 in)	1300 mm (51,2 in)
ENGINE	Kubota D1803-CR-T	Kubota D1803-CR-T	Kubota V2403-M	Kubota V2403-M



ARX 45-2

EU Stage V | U.S. EPA Tier 4F

ARX 45-2 C

EU Stage V | U.S. EPA Tier 4F

ARX 45-2

EU Stage IIIA / U.S. EPA Tier 4I

ARX 45-2 C

EU Stage IIIA / U.S. EPA Tier 4I

OPERATING WEIGHT	4395 kg (9690 lb)	4185 kg (9230 lb)	4405 kg (9711 lb)	4175 kg (9204 lb)
MAX. OPERATING WEIGHT	4685 kg (10 330 lb)	4485 kg (9890 lb)	4695 kg (10 351 lb)	4475 kg (9866 lb)
WORKING WIDTH	1380 mm (54.3 in)	1380 mm (54.3 in)	1380 mm (54.3 in)	1380 mm (54.3 in)
ENGINE	Kubota D1803-CR-T	Kubota D1803-CR-T	Kubota V2403-M	Kubota V2403-M

