

SMOOTH DRUM



ARS 30

EU Stage V | U.S. EPA Tier 4F

ARS 50

EU Stage V | U.S. EPA Tier 4F

ARS 70

EU Stage V | U.S. EPA Tier 4F

ASC 70

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	3480 kg (7670 lb)	4165 kg (9182 lb)	6490 kg (14,310 lb)	7140 kg (15 740 lb)
MAX. OPERATING WEIGHT	3770 kg (8310 lb)	4455 kg (9822 lb)	8400 kg (18,520 lb)	9260 kg (20 410 lb)
WORKING WIDTH	1200 mm (47,2 in)	1400 mm (55,1 in)	1680 mm (66.1 in)	1680 mm (66.1 in)
ENGINE	Kubota V2403-CR-T	Kubota V2403-CR-T	Kubota V3307-CR-TE5	Cummins - QSB3.3-C99



ARS 110

EU Stage V | U.S. EPA Tier 4F

ARS 110

EU Stage V | U.S. EPA Tier 4F

ARS 110

EU Stage IV | U.S. EPA Tier 4F

ARS 110.1

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	10 520 kg (23,193 lb)	10 860 kg (23,940 lb)	10 860 kg (23,940 lb)	11 400 kg (25,133 lb)
MAX. OPERATING WEIGHT	14 290 kg (31,504 lb)	14 630 kg (32,250 lb)	13 430 kg (29,610 lb)	13 317 kg (29,359 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)
ENGINE	Perkins 904J	Deutz TCD 3.6L4	Deutz TCD 3.6L4	Deutz TCD2012L042V



ARS 110.2

CEV Stage IV

ASC 110

EU Stage IIIA | U.S. EPA Tier 3

ARS 130

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	11 100 kg (24,471 lb)	11 490 kg (25 330 lb)		12 280 kg (27,073 lb)
MAX. OPERATING WEIGHT	-	15 370 kg (33 890 lb)		14 850 kg (32,739 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)		2130 mm (83,9 in)
ENGINE	Ashok Leyland H4C410122	Cummins QSB 4.5-C160		Perkins 904J



ARS 130

EU Stage V | U.S. EPA Tier 4F

ARS 130

EU Stage IV | U.S. EPA Tier 4F

ARS 130.1

EU Stage IIIA | U.S. EPA Tier 3

ASC 130

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	12 580 kg (27,730 lb)	12 580 kg (27,730 lb)	12 475 kg (27,503 lb)	12 510 kg (27 580 lb)
MAX. OPERATING WEIGHT	15 150 kg (33,400 lb)	15 150 kg (33,400 lb)	14 392 kg (31,729 lb)	16 390 kg (36 130 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)
ENGINE	Deutz TCD 3.6L4	Deutz TCD 3.6L4	Deutz TCD2012L042V	Cummins QSB 4.5-C160



ARS 150

EU Stage V | U.S. EPA Tier 4F

ARS 150

EU Stage V | U.S. EPA Tier 4F

ARS 150.1

EU Stage IIIA | U.S. EPA Tier 3

ASC 150

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	14 510 kg (31,989 lb)	14 840 kg (32,720 lb)	14 675 kg (32,353 lb)	14 580 kg (32 140 lb)
MAX. OPERATING WEIGHT	17 570 kg (38,735 lb)	17 410 kg (38,380 lb)	16 592 kg (36,579 lb)	18 460 kg (40 700 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)
ENGINE	Perkins 904J	Deutz TCD4.1 L4	Deutz TCD2013 L042V	Cummins QSB 4.5-C160



ARS 170

EU Stage V | U.S. EPA Tier 4F

ARS 170

EU Stage V | U.S. EPA Tier 4F

ARS 170.1

EU Stage IIIA | U.S. EPA Tier 3

ASC 170

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	16 140 kg (35,583 lb)	16 340 kg (36,020 lb)	15 825 kg (34,888 lb)	16 270 kg (35 870 lb)
MAX. OPERATING WEIGHT	18 750 kg (41,337 lb)	18 910 kg (41,690 lb)	17 742 kg (39,114 lb)	18 140 kg (39 990 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)
ENGINE	Perkins 904J	Deutz TCD4.1 L4	Deutz TCD2013 L042V	Cummins QSB 4.5-C160



ARS 200

EU Stage V | U.S. EPA Tier 4F

ARS 200

EU Stage IIIA | U.S. EPA Tier 3

ARS 220

EU Stage V | U.S. EPA Tier 4F

ARS 220

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	19 750 kg (43,540 lb)	19 750 kg (43,540 lb)	21 930 kg (48,350 lb)	21 630 kg (47,690 lb)
MAX. OPERATING WEIGHT	23 170 kg (51,080 lb)	23 170 kg (51,080 lb)	25 360 kg (55,910 lb)	25 050 kg (55,230 lb)
WORKING WIDTH	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)	2130 mm (83,9 in)
ENGINE	DEUTZ TCD 6.1 L6	DEUTZ TCD 6.1 L6	DEUTZ TCD 6.1 L6	DEUTZ TCD 6.1 L6