

PADFOOT DRUM

PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE
FOR PRODUCT AVAILABILITY IN YOUR MARKET.



ARS 30

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	3490 kg (7690 lb)
MAX. OPERATING WEIGHT	4500 kg (9920 lb)
WORKING WIDTH	1200 mm (47,2 in)
ENGINE	Kubota V2403-CR-T

ARS 50

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	4205 kg (9270 lb)
MAX. OPERATING WEIGHT	5340 kg (11773 lb)
WORKING WIDTH	1400 mm (55,1 in)
ENGINE	Kubota V2403-CR-T

ARS 70

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	6910 kg (15,230 lb)
MAX. OPERATING WEIGHT	8820 kg (19,440 lb)
WORKING WIDTH	1680 mm (66.1 in)
ENGINE	Kubota V3307-CR-TE5

ASC 70

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	7090 kg (15 630 lb)
MAX. OPERATING WEIGHT	8120 kg (17 900 lb)
WORKING WIDTH	1680 mm (66.1 in)
ENGINE	Cummins - QSB3.3-C99



ARS 110

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	11 145 kg (24,571 lb)
MAX. OPERATING WEIGHT	13 400 kg (29,542 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Perkins 904J

ARS 110

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	11 485 kg (25,320 lb)
MAX. OPERATING WEIGHT	13 740 kg (30,290 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD 3.6L4

ARS 110

EU Stage IV | U.S. EPA Tier 4F

OPERATING WEIGHT	11 485 kg (25,320 lb)
MAX. OPERATING WEIGHT	12 540 kg (27,650 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD 3.6L4



ASC 110

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	12 100 kg (26 680 lb)
MAX. OPERATING WEIGHT	14 280 kg (31 480 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Cummins QSB 4.5-C160

ARS 130

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	12 905 kg (28,451 lb)
MAX. OPERATING WEIGHT	13 960 kg (30,777 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Perkins 904J



ARS 130

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	13 205 kg (29,110 lb)
MAX. OPERATING WEIGHT	14 260 kg (31,440 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD 3.6L4

ARS 130

EU Stage IV | U.S. EPA Tier 4F

OPERATING WEIGHT	13 205 kg (29,110 lb)
MAX. OPERATING WEIGHT	14 260 kg (31,440 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD 3.6L4

ASC 130

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	12 740 kg (28 090 lb)
MAX. OPERATING WEIGHT	14 920 kg (32 890 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Cummins QSB 4.5-C160



ARS 150

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	14 830 kg (32,695 lb)
MAX. OPERATING WEIGHT	16 375 kg (36,101 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Perkins 904J

ARS 150

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	15 160 kg (33,420 lb)
MAX. OPERATING WEIGHT	16 215 kg (35,750 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD4.1 L4

ASC 150

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	14 490 kg (31 940 lb)
MAX. OPERATING WEIGHT	16 670 kg (36 750 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Cummins QSB 4.5-C160



ARS 170

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	16 355 kg (36,057 lb)
MAX. OPERATING WEIGHT	17 450 kg (38,471 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Perkins 904J

ARS 170

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	16 555 kg (36,500 lb)
MAX. OPERATING WEIGHT	17 610 kg (38,820 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Deutz TCD4.1 L4

ASC 170

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	16 170 kg (35 650 lb)
MAX. OPERATING WEIGHT	17 190 kg (37 900 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	Cummins QSB 4.5-C160



ARS 200

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	19 875 kg (43,820 lb)
MAX. OPERATING WEIGHT	20 980 kg (46,250 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	DEUTZ TCD 6.1 L6

ARS 200

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	19 875 kg (43,820 lb)
MAX. OPERATING WEIGHT	20 980 kg (46,250 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	DEUTZ TCD 6.1 L6

ARS 220

EU Stage V | U.S. EPA Tier 4F

OPERATING WEIGHT	22 060 kg (48,630 lb)
MAX. OPERATING WEIGHT	23 170 kg (51,080 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	DEUTZ TCD 6.1 L6

ARS 220

EU Stage IIIA | U.S. EPA Tier 3

OPERATING WEIGHT	21 760 kg (47 970 lb)
MAX. OPERATING WEIGHT	25 180 kg (55,510 lb)
WORKING WIDTH	2130 mm (83,9 in)
ENGINE	DEUTZ TCD 6.1 L6